

CLAIMS

What is claimed is:

- 5 *Sub 924* 1. An air spring for a vehicle air suspension system comprising:
a piston attached to a longitudinal member pivotally attached to a chassis
component for pivotal movement about an axis; and
an air cell having a first end attached to said piston and a second end attached
to said chassis component, said second end having a greater diameter than said first
end.
- 10
2. The air spring as recited in claim 1, wherein said air cell is tapered between
said first end and said second end.
3. The air spring as recited in claim 1, wherein said air cell is of a frustro-
15 conical configuration.
4. An air suspension system for a vehicle comprising:
a longitudinal member pivotally attached to a chassis component for pivotal
movement about an axis;
20 an axle assembly mounted to said longitudinal member; and
an air spring having a frustro-conical air cell and a piston, said air spring
disposed between said longitudinal member and said chassis component, said air cell
having a first end attached to said piston and a second end attached to said chassis
component.

25

Sub
939

The system as recited in claim 4, wherein said air cell includes an anti-vacuum system and a damper extendable at a rate which allows said anti-vacuum system to equalize a pressure within said air cell with atmospheric pressure as said longitudinal member pivots about said axis away from said chassis component.

5

6. An air suspension system for a vehicle comprising:

a longitudinal member pivotally attached to a chassis component for pivotal movement about an axis;

an axle assembly mounted to said longitudinal member;

10

an air spring having a frustro-conical air cell and a piston, said air spring disposed between said longitudinal member and said chassis component, said air cell having a first end attached to said piston and a second end attached to said chassis component;

15

an anti-vacuum system within said air spring, said anti-vacuum system operable to equalize a pressure within said air cell with atmospheric pressure as said longitudinal member pivots about said axis away from said chassis component; and

20

a damper disposed between said longitudinal member and the vehicle, said damper extendable at a rate which allows said anti-vacuum system to equalize a pressure within said air cell with atmospheric pressure as said longitudinal member pivots about said axis away from said chassis component.

60130-391
EL491262985US